



## Everest Printer Specifications

Item	Description
<b>Printing Speed(including tray cycle time)</b>	60 seconds or less for CMY color coverage. 66 seconds for CMY+W First print is 5 minutes, which includes warm-up time
<b>Printing Modes</b>	Monochrome, CMY, and CMY+W
<b>Print Quality</b>	Equivalent of 300 DPI (dots per inch) using variable dot technology
<b>Media Types</b>	CDs or DVDs with Everest-compatible coating
<b>Ribbons</b>	Monochrome (Black) CMY (Cyan, Magenta, and Yellow)
<b>Ribbon Capacity</b>	Retransfer Ribbon = 1000 discs or 500 discs Black Ribbon = 1000 discs CMY Ribbon = 500 discs
<b>Physical Properties</b>	9.7" H x 9.4" W x 14.8" D (24.6 cm x 24.0 cm x 37.5 cm) Depth with print tray extended – 22.25" (56.5 cm) Left side cover open for print ribbon replacement – add additional 9.1" (23 cm) Weight: 40.8 lbs (18.5 Kg) Weight with packaging: 50.7 lbs (23Kg)
<b>Interface</b>	USB 2 (Universal Serial Bus) – B type connector
<b>Power</b>	100 – 120V 500W / 220 – 240V 500W 50 / 60 Hz (manual switching)
<b>Operating Temperature</b>	59° F to 86° F (15° C to 30° C)
<b>Relative Humidity</b>	30% to 70% non-condensing
<b>Operating Temperature</b>	60° F to 90° F (15.5° C to 35° C)
<b>Relative Humidity</b>	30% to 80% non-condensing
<b>Minimum System Requirements Windows-based PC</b>	Pentium 300 or better with 128MB RAM Windows 2000 Professional or XP Professional USB port
<b>Minimum System Requirements Macintosh Computer</b>	G3 or better with 128 MB RAM Macintosh OS X version 10.3/10.4 USB port